Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A method for training a system to inspect a spatially distorted pattern, the method comprising:

receiving a digitized image of an object, the digitized image including a region of interest;

dividing the region of interest in its entirety into a plurality of non-overlapping sub-regions, a size of each of the non-overlapping sub-regions being small enough such that a conventional an image-based inspecting method can reliably inspect each of the sub-regions;

training a fine search tool and an image-based inspection tool for a respective single model for each of the plurality of non-overlapping sub-regions;

building a single search tree for determining an order for inspecting each non-overlapping sub-region of the plurality of non-overlapping sub-regions at a run-time; and

training a coarse alignment tool for the region of interest in its entirety so as to enable providing at run time an approximate location for a root sub-region of the single search tree.

Claim 2 (currently amended): The method according to claim 1, wherein the size of each of the non-overlapping sub-regions is small enough such that each of the sub-regions is ~~well-approximated~~ well-approximated by an affine transformation.

Claim 3 (currently amended): The method of claim 1, wherein the building of the single search tree comprises:

establishing the order so that ~~transformation~~ location information for located ones of the non-overlapping sub-regions is used to minimize a search range for neighboring ones of the non-overlapping sub-regions.

Claim 4 (currently amended): The method of claim 1, wherein the training of the fine search tool for the respective single model for each of the plurality of non-overlapping sub-regions is performed by using a correlation search.

Claim 5 (currently amended): The method of claim 1, wherein the training of the image-based inspection tool for the respective single model for each of the plurality of non-overlapping sub-regions is performed by using a golden template comparison method.

Claim 6 (currently amended): A method for inspecting a spatially distorted pattern, the method comprising:

running a coarse alignment tool to approximately locate the <u>spatially distorted</u> pattern <u>in its entirety</u> within a region of interest <u>so as to provide an approximate location for a root sub-region of a single search tree</u>;

<u>running a fine alignment tool in an order according to the single search tree,</u> ~~using search tree information of a single search tree~~ and ~~an~~ <u>using the</u> approximate location of a <u>the</u> root sub-region~~, found by the coarse alignment tool,~~ to locate ~~, sequentially in an order according to the search tree information,~~ a plurality of <u>non-overlapping</u> sub-regions within the region of interest <u>so as to provide fine location information</u>, the <u>non-overlapping</u> sub-regions covering the region of interest in its entirety, each of the <u>non-overlapping</u> sub-regions being of a size small enough such that a ~~conventional~~ <u>an image-based</u> inspecting method can reliably inspect each of the <u>non-overlapping</u> sub-regions using respective single models;

inspecting each of the <u>non-overlapping</u> sub-regions <u>using the fine location information and the image-based inspecting method</u> so as to produce a difference image for each of the <u>non-overlapping</u> sub-regions.

4

Claim 7 (currently amended): The method of claim 6, further comprising:

comparing the fine location information with model location information so as to provide a distortion vector for each non-overlapping sub-region;

combining all ~~location information~~ distortion vectors, one for each non-overlapping sub-region, so as to produce a distortion vector field ~~for each of the sub-regions~~; and

using the distortion vector ~~fields~~ field to make a pass/fail decision based on user-specified tolerances.

Claim 8 (currently amended): The method of claim 6, wherein:

the inspecting using the fine location information and the image-based inspecting method produces a match image for each of the non-overlapping sub-regions, the method further comprising:

combining the difference images for each of the non-overlapping sub-regions into a single difference image; and

combining the match images for each of the non-overlapping sub-regions into a single match image.

Claim 9 (currently amended): The method of claim 7, wherein:

the inspecting <u>using the fine location information and the image-based inspecting method</u> produces a difference image for each of the <u>non-overlapping</u> sub-regions and a match image for each of the <u>non-overlapping</u> sub-regions, the method further comprising:

combining the difference images for each of the <u>non-overlapping</u> sub-regions into a single difference image;

combining the match images for each of the <u>non-overlapping</u> sub-regions into a single match image;

<u>comparing the fine location information with model location information so as to provide a distortion vector for each non-overlapping sub-region;</u> and

combining all ~~locations information~~ <u>distortion vectors, one for each non-overlapping sub-region, so as</u> to produce a distortion vector field ~~for each of the sub-regions~~.

6

Claim 10 (currently amended): The method according to claim 6, wherein the size of each of the non-overlapping sub-regions is small enough such that each of the non-overlapping sub-regions is well approximated by an affine transformation.

Claim 11 (currently amended): The method of claim 6, further comprising:

using ~~transformation~~ the fine location information from located ones of the non-overlapping sub-regions to interpolate ~~transformation~~ location information for a non-overlapping sub-region when the non-overlapping sub-region cannot be located; and

inspecting the non-overlapping sub-region based on the interpolated ~~transformation~~ location information.

Claim 12 (currently amended): The method of claim 6, further comprising:

using ~~the~~ respective <u>single</u> models for at least some of the <u>non-overlapping</u> sub-regions to determine respective ~~transformation~~ <u>fine location</u> information; and

predicting ~~registration results~~ <u>fine location information</u> in at least one of the non-overlapping sub-regions by using the respective ~~transformation~~ <u>fine location</u> information of neighboring ones of the at least some of the <u>non-overlapping</u> sub-regions when <u>the at least one of the non-overlapping sub-regions cannot be located by running the fine alignment tool</u> ~~training of the search tool for the respective single model for the at least one of the sub-regions was not successfully performed~~.

Claim 13 (currently amended): The method of claim 6, wherein the inspecting of each of the <u>non-overlapping</u> sub-regions <u>using an image-based inspecting method</u> is performed by a golden-template comparison method.

Claim 14 (currently amended): An apparatus for inspecting a spatially distorted pattern, the apparatus comprising:

a memory for storing a digitized image of an object;

a region divider for dividing the digitized image of a region of interest in its entirety into a plurality of non-overlapping sub-regions, the non-overlapping sub-regions covering the region of interest completely, a size of each of the non-overlapping sub-regions being small enough such that a conventional an image-based inspecting method can reliably inspect each of the non-overlapping sub-regions;

a coarse alignment mechanism tool for approximately locating the pattern so as to provide an approximate location for a root sub-region of a single search tree;

a fine search mechanism tool for locating each of the non-overlapping sub-regions sequentially in an order based on a the single search tree; and

an image-based inspector for inspecting each of the non-overlapping sub-regions.

9

Claim 15 (currently amended): The apparatus of claim 14, further comprising:

a vector field producer to combine all location information to produce a

distortion vector field for each of the non-overlapping sub-regions; and

a comparing mechanism for using the distortion vector field to make a

pass/fail decision based on user specified tolerances.

Claim 16 (currently amended): The apparatus of claim 14, wherein:

the image-based inspector for inspecting each of the non-overlapping sub-

regions produces a difference image for each of the non-overlapping sub-regions

and a match image for each of the non-overlapping sub-regions, the apparatus

further comprises:

a first combiner for combining the difference images for each of the non-

overlapping sub-regions into a single difference image; and

a second combiner for combining the match images for each of the non-

overlapping sub-regions into a single match image.

Claim 17 (currently amended): The apparatus according to claim 14, wherein the

size of each of the non-overlapping sub-regions is small enough such that each

of the non-overlapping sub-regions is ~~well-approximated~~ well-approximated by an

affine transformation.

Claim 18 (currently amended): The apparatus of claim 14, further comprising:

an ~~interpolation~~ interpolator for using ~~transformation~~ location information

from located ones of the non-overlapping sub-regions to interpolate

~~transformation~~ location information for a non-overlapping sub-region when the

non-overlapping sub-region cannot be located by the fine search ~~mechanism~~

tool; wherein

the image-based inspector inspects the non-overlapping sub-region based

on the interpolated ~~transformation~~ location information.

Claim 19 (currently amended): The apparatus of claim 14, further comprising:

an interpolator for using the respective models for at least some of the

non-overlapping sub-regions to determine respective ~~transformation~~ location

information, and for predicting ~~registration results~~ location information in at least

one of the non-overlapping sub-regions by using the respective ~~transformation~~

location information of neighboring ones of the at least some of the non-

overlapping sub-regions when the at least one of the non-overlapping sub-

regions cannot be located ~~training of the respective single model for the at least~~

~~one of the sub-regions was not successfully performed~~.

Claim 20 (currently amended): The apparatus of claim 14, wherein the image-

based inspector inspects each of the non-overlapping sub-regions by using a

golden-template comparison method.

Claim 21 (currently amended): An apparatus for inspecting a spatially distorted pattern, the apparatus comprising:

a storage for storing a digitized image of an object, the digitized image including a region of interest;

a region divider for dividing the region of interest in its entirety into a plurality of non-overlapping sub-regions, a size of each of the non-overlapping sub-regions being small enough such that a conventional an image-based inspecting method can reliably inspect each of the non-overlapping sub-regions;

a trainer for training a respective single model for a fine search tool and for an image-based inspection tool inspector for each of the plurality of non-overlapping sub-regions;

a search tree builder for building a single search tree for determining an order for image-based inspecting of each sub-region of the plurality of non-overlapping sub-regions at a run time;

a course alignment trainer;

a course alignment mechanism tool for approximately locating the pattern so as to provide an approximate location for a root sub-region of a single search tree, the coarse alignment mechanism tool being configured to be trained by the coarse alignment trainer;

a fine search mechanism tool for locating each of the non-overlapping sub-regions sequentially in an order based on the single search tree, a the root

12

sub-region <u>of the single search tree</u> being provided by the coarse alignment

~~mechanism~~ <u>tool</u>; and

an <u>image-based</u> inspector for inspecting each of the <u>non-overlapping</u> sub-

regions.

Claim 22 (currently amended): The apparatus according to claim 21, further

comprising:

a vector field producer to combine all location information to produce a

distortion vector field for each of the <u>non-overlapping</u> sub-regions; and

a comparing mechanism for using the distortion vector fields to make a

pass/fail decision based on user specified tolerances.

Claim 23 (currently amended): The apparatus of claim 21, wherein:

the <u>image-based</u> inspector produces a difference image for each of the

<u>non-overlapping</u> sub-regions and a match image for each of the <u>non-overlapping</u>

sub-regions, the apparatus further comprises:

a first combiner for combining the differences images for each of the <u>non-</u>

<u>overlapping</u> sub-regions into a single difference image; and

a second combiner for combining the match images for each of the <u>non-</u>

<u>overlapping</u> sub-regions into a single match image.

Claim 24 (currently amended): The apparatus according to claim 21, wherein the size of each of the non-overlapping sub-regions is small enough such that each of the non-overlapping sub-regions is well approximated by an affine transformation.

Claim 25 (currently amended): The method of claim 21, wherein the building of the single search tree comprises:

establishing the order so that ~~transformation~~ location information for located ones of the non-overlapping sub-regions is used to minimize a search range for neighboring ones of the non-overlapping sub-regions.

Claim 26 (currently amended): The apparatus of claim 21, further comprising:

an interpolator for using ~~transformation~~ location information from located ones of the non-overlapping sub-regions to interpolate ~~transformation~~ location information for a non-overlapping sub-region when the sub-region cannot be located, wherein

the image-based inspector inspects the previously unlocated non-overlapping sub-region based on the interpolated ~~transformation~~ location information.

14

Claim 27 (currently amended): A medium having a stored therein machine-readable information, such that when the machine-readable information is read into a memory of a computer and executed, the machine-readable information causes the computer:

to receive a digitized image of an object, the digitized image including a region of interest;

to divide the region of interest in its entirety into a plurality of non-overlapping sub-regions, a size of each of the non-overlapping sub-regions being small enough such that a conventional an image-based inspecting method can reliably inspect each of the non-overlapping sub-regions;

to train a respective single model for a fine search tool and for an image-based inspection tool for each of the plurality of non-overlapping sub-regions;

to build a single search tree for determining an order for inspecting the plurality of non-overlapping sub-regions at a run-time; and

to train a respective model for a coarse alignment tool so as to enable providing at run time an approximate location for a root sub-region of the single search tree.

Claim 28 (currently amended): The medium of claim 27, wherein when building the single search tree, the machine-readable information causes the computer:

to establish the order so that ~~transformation~~ location information for located ones of the non-overlapping sub-regions is used to minimize a search range for neighboring ones of the non-overlapping sub-regions.

Claim 29 (currently amended): The medium of claim 27, wherein the machine-readable information further causes the computer:

to run a coarse alignment tool to approximately locate a pattern so as to provide an approximate location for a root sub-region of a single search tree.;

to run a fine alignment tool in an order according to the single search tree ~~to use information from a search tree~~ and a using the approximate location of the root sub-region approximately located by the coarse alignment tool to locate a plurality of non-overlapping sub-regions so as to provide fine location information ~~sequentially in an order according to the information from the search tree~~, each of the non-overlapping sub-regions being of a size small enough such that a ~~conventional~~ image-based inspecting method can reliably inspect each of the non-overlapping sub-regions; and

to perform image-based ~~inspect~~ inspection of each of the non-overlapping sub-regions to produce a difference image for each of the non-overlapping sub-regions and a match image for each of the non-overlapping sub-regions.

Claim 30 (currently amended): The medium of claim 29, wherein the machine-readable information further causes the computer:

to combine the difference images for each of the <u>non-overlapping</u> sub-regions into a single difference image; and

to combine the match images for each of the <u>non-overlapping</u> sub-regions into a single match image.

Claim 31 (currently amended): The medium of claim 29, wherein the machine-readable information further causes the computer:

<u>to compare the fine location information with model location information so as to provide a distortion vector for each non-overlapping sub-region;</u>

to combine all ~~location information~~ <u>distortion vectors, one for each non-overlapping sub-region, so as</u> to produce a distortion vector field ~~for each of the sub-regions~~; and

to use the distortion vector ~~fields~~ <u>field</u> to make a pass/fail decision based on user-specified tolerances.

Claim 32 (currently amended): The medium of claim 27, wherein the machine-readable information further causes the computer:

to use ~~transformation~~ fine location information from located ones of the non-overlapping sub-regions to interpolate ~~transformation~~ fine location information for a non-overlapping sub-region when the non-overlapping sub-region cannot be located; and

to run ~~a search~~ an image-based inspection tool on the non-overlapping sub-region based on the interpolated ~~transformation~~ fine location information.

Claim 33 (currently amended): The method of claim 6, further comprising:

dividing one of the non-overlapping sub-regions into a plurality of smaller non-overlapping sub-regions when the one of the non-overlapping sub-regions cannot be located using a fine search tool.

Claim 34 (currently amended): A method for inspecting a spatially distorted pattern, the method comprising:

running a coarse alignment tool to approximately locate the pattern so as to provide an approximate location for a root sub-region of a single search tree;

running a fine alignment tool in an order according to the single search tree, using search tree information and an and using the approximate location of a the root sub-region, found by the coarse alignment tool, to locate a plurality of non-overlapping sub-regions so as to provide fine location information sequentially in an order according to the search tree information, each of the non-overlapping sub-regions being of a size small enough such that a convention an image-based inspecting method can reliably inspect each of the non-overlapping sub-regions;

comparing the fine location information with model location information so as to provide a distortion vector for each non-overlapping sub-region;

combining all location information distortion vectors, one for each non-overlapping sub-region, so as to produce a distortion vector field for each of the sub-regions; and

using the distortion vector fields field to make a pass/fail decision based on user-specified tolerances.

19

Claim 35 (currently amended): An apparatus for inspecting a spatially distorted

pattern, the apparatus comprising:

a memory for storing a digitized image of an object;

a region divider for dividing the digitized image of a region of interest in its

entirety into a plurality of non-overlapping sub-regions, a size of each of the non-

overlapping sub-regions being small enough such that a conventional an image-

based inspecting method can reliably inspect each of the non-overlapping sub-

regions;

a coarse alignment mechanism tool for approximately locating the pattern

so as to provide an approximate location for a root sub-region of a single search

tree;

a fine search mechanism tool for locating each of the non-overlapping

sub-regions sequentially in an order based on the single search tree so as to

provide fine location information;

a vector field producer to for comparing the fine location information with

model location information so as to provide a distortion vector for each non-

overlapping sub-region, and for combining the distortion vectors combine all

location information to produce a distortion vector field for each of the sub-

regions; and

a comparing mechanism for using the distortion vector field to make a

pass/fail decision based on user specified tolerances.

20

Claim 36 (currently amended): A medium having stored therein machine-readable information, such that when the machine-readable information is read into a memory of a computer and executed, the machine-readable information causes the computer:

to run a coarse alignment tool to approximately locate a pattern so as to provide an approximate location for a root sub-region of a single search tree;

to ~~use~~ run a fine alignment tool in an order according to ~~information from a~~ the single search tree ~~and a~~ using the root sub-region approximately located by the coarse alignment to locate a plurality of non-overlapping sub-regions so as to provide fine location information ~~sequentially in an order according to the information from the search tree~~, each of the non-overlapping sub-regions being of a size small enough such that ~~a convention~~ an image-based inspecting method can reliably inspect each of the non-overlapping sub-regions;

to compare the fine location information with model location information so as to provide a distortion vector for each non-overlapping sub-region;

to combine all ~~location information~~ distortion vectors , one for each non-overlapping sub-region, so as to produce a distortion vector field ~~for each of the sub-regions~~; and

to use the distortion vector ~~fields~~ field to make a pass/fail decision based on user-specified tolerances.